

DIN-Rail Embedded Controller

SEC2

Datasheet



IPCOMM GmbH

Gundstraße 15
91056 Erlangen
Germany

Phone: +49 9131 92076-0
Fax: +49 9131 92076-10
Internet: <http://www.ipcomm.de>
Email: info@ipcomm.de

Edition September 2010
Version 1.2.3



DIN EN ISO 9001:2008
Zertifikat: 01 100 040757

Technical Data

General

- No rotating parts

Processor

- 400 MHz CPU

Dynamic Memory

- 128 MB SDRAM

Network Interface

- 1x RJ-45 for 10/100Base-T
- Protection: 1.5KV magnetic isolation

Serial Ports

- 1x RJ45 for RS232/422/485
- 3x RJ45 for RS232 / RS485 (without DTR, DCD und DSR signal)
- Baud rate: up to 921.6 Kbps
- Parity: None, Even, Odd, Mark, Space
- Data Bits: 5,6,7,8
- Stop Bit: 1, 1.5, 2 bits
- Flow Control: RTS/CTS, XON/XOFF, None

USB Ports

- 2x USB 2.0 compliant, supports low speed (1.5Mbps) and full- speed (12Mbps) data rate

Diagnostic LEDs

- Power
- Software state (CPU-LED)
- Link and activity for LAN interface
- Transmit and receive LEDs for the RS232 interfaces

Mass Storage

- 128 MB Flash

Additional Functions

- Battery buffered real time clock (RTC)
- Watchdog
- Reset
- GPIO
- Serial Console Interface

Power Input /Power consumption

- 9 - 48 V DC / 4 W max.

Standards

- CE Class A, FCC Class A

Housing

- steel chassis, including clip for mounting on a 35 mm DIN-Rail

Dimensions (without clip)

- 78 x 108 x 24mm (W/H/D)

Weight

- 0,4 kg

Operating Environment

- Operating / storage Temperature: 0°C – 70°C / -20 – 80°C
- Relative humidity: 5 % to 95 % non-condensing

Note: Differences to the delivered type are possible.